



TRACK AND SPOTS FOCUS


- Compact adjustable track mounted spotlight
- Die-cast construction
- Three circuit track adaptor as standard
- Supplied with integral non-dimming driver
- Ideal for decorative retail applications
- Glare control accessories available

400/700/1000/1300/2000lm CRI 80+
400/700/1000/1300lm CRI 98



Accessories

To order, use the following suffix



- /HL Honeycomb louvre
 - /CG Clear Glass
 - /SL Softening Lens
 - /RD Rotary Dimming
- Allows individual dimming on standard track

PRODUCT CODE

Lumen Output:

(04)	400 lm
(07)	700 lm
(10)	1000 lm
(13)	1300 lm
(20)	2000 lm

Colour Temps:

(27)	2700K
(30)	3000K
(35)	3500K
(40)	4000K

(3500K available in 700 lumens and above)

Colour Rendering:

(V8)	Vibrancy 80
(V9)	Vibrancy 98
(80)	CRI 80+
(98)	CRI 98

(CRI 98 / V9 up to 1300 lumens)

Beam Angles:

(S)	Spot: 10°
(N)	Narrow: 20°
(M)	Medium: 40°
(W)	Wide: 60°

(10° up to 1300lm CRI 80 & 1300 CRI 98)

Colour:

(W)	White
(B)	Black

FO _____ /**

Options:

Dimming:

- /DT Trailing Edge
- /DL Leading Edge

(Other dimming options available see page 123)

