


**100 SERIES**

# UNIVERSAL FIRE RATED

- Fire rated circular downlight
- 1 hour fire protection
- Die-cast construction
- Compliant with Building Regulations
- Part B – BS 476 / BS EN 13665
- Supplied with pre-wired non dimmable driver



## PRODUCT CODE

**Lumen Output:**

_____	(04)	400 lm
_____	(07)	700 lm
_____	(10)	1000 lm
_____	(13)	1300 lm

**Colour Temps:**

_____	(27)	2700K
_____	(30)	3000K
_____	(35)	3500K
_____	(40)	4000K

*(3500K available in 700 lumens and above)*

**Colour Rendering:**

_____	(V8)	Vibrancy 80
_____	(V9)	Vibrancy 98
_____	(80)	CRI 80+
_____	(98)	CRI 98

*(CRI 98 / V9 up to 1000 lumens)*

**Beam Angles:**

_____	(N)	Narrow: 20°
_____	(M)	Medium: 40°
_____	(W)	Wide: 60°

**Colour:**

_____	(W)	White
-------	-----	-------

**F6** \_\_\_\_\_ / \*\* / \*\*

**Options:**

- Dimming:**
- /DT Trailing Edge
  - /DL Leading Edge
  - /DD DALI
  - /DA Analogue (1-10V)
  - /LT Lumentalk
  - /M3 3Hrs Maintained
  - /ST Self Test
  - /DE DALI Emergency

*(Other dimming options available see page 123)*

